

Injectable Safe-Strip

Product Number: 883



What does Gemini Injectable Safe-Strip do?

Gemini Injectable Safe-Strip removes semi-transparent stains and wood sealers by dissolving old finishes. New technology allows Gemini Injectable Safe-Strip to be applied with either a pressure washer or diluted for use with a [TWP® Deck Sprayer](#).

Features:

- New application technology allowing pressure washer injection
- Removes oil-based and water-based semi-transparent stains and sealers
- Restores weathered wood to natural color
- 100% Biodegradable – will not harm plants or pets
- Does not contain chlorine bleach that may damage wood fibers
- Use on all exterior wood surfaces including decks, fences and fascia

Surface Preparation:

Injecting:

1. Put injector hose into undiluted Injectable Safe-Strip container. Inject desired working area (200-300 sq. ft. recommended). *Injector ratio 12:1 or lower.*
2. Although Injectable Safe-Strip has little or no dwell time, 5 minutes of product working time is recommended. Pressure wash working area thoroughly.

Ready-to-use:

1. Pour Injectable Safe-Strip into container. Add 4 parts water (1 gallon makes 5 gallons, 5 gallons makes 25 gallons). Apply liberally to wood surfaces. Best application results are with a [TWP® Deck Sprayer](#). After application, always keep working area moist during surface preparation.
2. Once applied you may begin to scrub (*NO SCRUBBING NECESSARY WITH USE OF PRESSURE WASHER*). When scrubbing applied area, use synthetic, stiff bristle brush; do not use a wire or natural bristle brush.
3. Rinse thoroughly with hose or pressure washer. A pressure washer will show the best results.

*** Use caution when using Safe Strip. Wet surfaces will be slippery.**

Coverage Rate: Approximately 500-1000 square feet per gallon.