

## WOODSMAN

### A Waterborne Sealant for Use During Log Stacking

Woodsman is an internal sealant and adhesive that is applied between logs during construction. With better stretch and adhesion than other sealants, Woodsman is ideal for providing a long-lasting barrier against insects, air and water infiltration between the logs.



Woodsman is easy to apply using standard caulk application equipment. Its extended shelf life makes those jobs that take longer than expected more manageable. Since Woodsman cleans up with just soap and water, job site labor costs are decreased.

### Woodsman Colors



### Features and Statistics

- **Eliminates air and water infiltration**
- **Economical**
- **Highly elastic**
- **Longer shelf life**
- **Light tan in color**

<b>Shelf Life</b>	<ul style="list-style-type: none"><li>• <b>1 year</b></li></ul>
-------------------	---

<b>Application Temperature</b>	<ul style="list-style-type: none"> <li>• 40° to 90°</li> </ul>
<b>Application Methods</b>	<ul style="list-style-type: none"> <li>• Caulking Gun (Air, Bulk, Loading, Standard, Commercial)</li> </ul>
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>• Clean and Dry</li> </ul>
<b>Frequency</b>	<ul style="list-style-type: none"> <li>• Once</li> </ul>
<b>Special Instructions</b>	<ul style="list-style-type: none"> <li>• Follow log manufacturer's instructions</li> <li>• See application guide</li> </ul>
<b>Drying Time</b>	<ul style="list-style-type: none"> <li>• Dries inside the wall for a tight seal</li> </ul>

**Woodsman Price List**

<b>WOODSMAN Sizes</b>
<b>30 oz. tubes (Case of 10) 31 lb.</b>
<b>11 oz. tubes (Case of 12) 14 lb.</b>



<b>Woodsman Coverage Rates</b>		
Diameter of Bead	Feet per 11-oz.tube	Feet per 30-oz. tube
1/4"	32'	92'
3/8"	14'	41'
1/2"	8'	23'