Solid-Strip

Product Number: 893 (Available in gallons only)

What does Gemini Solid-Strip do?



Gemini Solid-Strip is designed for industrial strength stripping. It will remove heavy coated finishes and is ideal for solid color stains, water-based and latex paints. Use Gemini Solid-Strip on decks, logs, or any wood surface that needs restoring. (For 100% acrylic water-based products, use a conventional paint stripper)

Features:

- Prepares wood surface for any type of re-coating
- Removes weathered stains and wood sealers
- Removes oil, latex and water-based finishes
- Tackles the tough stripping jobs
- Easy application and removal

Surface Preparation:

Easy 3 Step Application Process:

- 1. Pre-wet and cover the surrounding work area and vegetation to ensure no damage occurs. Apply Solid-Strip liberally to wood surfaces (always test a small inconspicuous area to see if the desired result will be achieved). Best application results are with a TWP* Deck Sprayer, although a brush or roller can also be used.
- 2. Solid-Strip should sit for a minimum of 15 minutes, however, do not allow product to dry. After sitting you may begin to scrub. When scrubbing applied area, use synthetic, stiff bristle brush (do not use a wire or natural bristle brush).
- 3. Rinse thoroughly with hose or pressure washer. A pressure washer will show the best results, however, do not exceed 1000 P.S.I.
 - If not used properly a pressure washer may damage wood.
 - Do not allow product to dry. If stubborn areas persist, re-apply Solid-Strip and follow steps 2 and 3.

• Wood may darken after stripping. Use Gemini's Wood Brightener for Cedar and Redwood to revive color.

NOTE: Use caution when working with Solid-Strip, wet surfaces will be slippery. See label for precaution statement.

Coverage Rate: Approximately 100-200 square feet per gallon.