

## PERMA-CHINK

### Log Home Sealant

Since 1981, Perma-Chink Log Home Sealant has proven itself on thousands of chinked and chinkless style homes to become the most widely applied chinking in the world. It's simply the best chinking by every measure: longevity, appearance, performance and ease of application.



Perma-Chink is a flexible, textured chinking that seals the open gaps between logs to eliminate heat loss and air infiltration. Even though it looks and feels like traditional mortar, it's not. Perma-Chink is a pure acrylic that adheres to logs and stretches to maintain a tight seal by following log movement.

Like all of our products, Perma-Chink is easy to apply and comes backed by the support of our knowledgeable, friendly staff. When you use Perma-Chink, professional advice is never more than a phone call away.

Application can be done by the homeowner or a professional contractor. We stock a full line of application accessories or can refer a professional applicator in your area.

### Perma-Chink Colors



### Features and Statistics

- Eliminates air and water infiltration
- For interior and exterior walls
- Stays flexible to follow movement of logs
- Suitable for all climates

<b>Shelf Life</b>	<ul style="list-style-type: none"> <li>• 1 year</li> </ul>
<b>Application Temperature</b>	<ul style="list-style-type: none"> <li>• 40° to 90°</li> </ul>
<b>Application Methods</b>	<ul style="list-style-type: none"> <li>• <a href="#">Chink Pump</a></li> <li>• Caulking Gun (Air, Bulk, Loading, Standard, Commercial) <i>see</i> <a href="#">Tools</a></li> <li>• Application Bag</li> </ul>
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>• Clean and Dry</li> <li>• Backing material</li> <li>• Bond breaker tape on bare wood</li> </ul>
<b>Frequency</b>	<ul style="list-style-type: none"> <li>• One time application</li> </ul>
<b>Special Instructions</b>	<ul style="list-style-type: none"> <li>• Apply approximately 3/8" thickness</li> <li>• Avoid application in direct sunlight</li> <li>• Seam width should be 1/6 of log diameter</li> </ul>
<b>Drying Time</b>	<ul style="list-style-type: none"> <li>• Skins over in 1 to 2 hours.</li> <li>• Cures in 2 to 8 weeks depending on temperature and humidity</li> </ul>

### Perma-Chink Quantity List

<b>PERMA-CHINK</b>
<b>5 gal (53 lb.) pail</b>
<b>30 oz. tubes (Case of 10) 35 lb.</b>
<b>11 oz. tubes (Case of 12) 14 lb.</b>



<b>Perma-Chink Coverage Rates</b>	
<i>To be Applied approximately 3/8" thickness.</i>	
<b>Width of gap</b>	<b>Feet per pail</b>
1/2"	Use Energy Seal
3/4"	Use Energy Seal
1"	385'
1.5"	256'
2"	192'

2.5"	154'
3"	127'
3.5"	110'
4"	96'
4.5"	85'
5"	76'
6"	63.5'